

HDMI TO HDMI+UVC +USB2.0



Product Introduction

Devicewell's UD series product UD1005 is a device with UVC output that facilitates terminal image capture.

UD1009 is a live broadcast auxiliary device developed for the general live broadcast market. Through HDMI signal input, the commonly used HDMI signal can be easily connected to the computer, which is convenient for users to flexibly access their own live broadcast platform. The device supports UVC+UAC function. It is connected to the PC device through the output signal, and connected to the OBS software, so that the audio and video of the live screen can be transmitted to the audience in high-definition 1080P streaming media content.

The device is equipped with a Micro usb interface for device power supply, which can be applied to USB mobile device power supply systems such as charging treasure. In addition, the equipment is equipped with 1/4 hot shoe screw, which is convenient for professional users to fix the equipment.

Product Features

- ◆ HDMI to UVC/UAC
- ◆ Support UVC protocol output
- ◆ No need for external power supply, USB internal power supply can
- ◆ Support interlace to progressive
- ◆ Support Windows, Android and other OS

Interface Description



NO.	Features	NO.	Features
1	HDMI input	3	UVC output
2	USB Power supply	4	HDMI output

Product Parameters

ver:1.0

Name	UVC output image capture converter	
Model	UD1009	
HDMI Signal Input	Input signal	Standard HDMI signal
	Connector	HDMI
	Bit rate	270Mbps~2.97Gbps
	Signal amplitude	800mV ± 10%(HDMI)
	Impedance	100Ω
HDMI Signal Output	Output signal	Standard HDMI signal
	Impedance	100Ω
	Signal amplitude	800mV ± 10%
	Connector	HDMI
Common Parameters	Power supply	DC 5V
	Power	<3W
	Size	50*45*25mm
	Weight	0.1 KG
	Working temperature	0℃~50℃ no condensation
	Storage temperature	-20℃~75℃
	Storage humidity	0%~90%RH, no condensation

Size



Application

